SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

MSDS Name : Paradise Visage Passion Adhesive

Company Identification : Paradise Visage Kft., Hungary, Budapest, 1191, Eotvos utca 16.

SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	Wt%	CAS Registry No	Chemical Formula
Ethyl cyanoacrylate	91.1	7085-85-0	CH2C(CN)COOC2H5
PMMA	6.9	secret	secret
Carbon black	2	1333-86-4	

SECTION 3 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW :

Vapor is irritating to eyes, skin and mucous membranes and respiratory tract.

POTENTIAL HEALTH EFFECTS :

May cause sensitization by inhalation. Narcotic effects, headache, dizziness, vomiting.

Skin: dryness Eye: irritation

POTENTIAL ENVIROMENTAL EFFECTS : Not available.

SIGN AND SYMPTOMS OF EXPOSURE:

Vapor is irritating to eyes and mucous membranes above TLV.

Prolonged and repeated overexposure to vapors may produce symptoms of non-allergic asthma in sensitive individuals.

EXISTING CONDITIONS AGGRAVATED BY EXPOSURE: Unknown

TARGET ORGAN AND OTHER HEALTH EFFECTS: *Literature Referenced

Ingredients Ethylcyanoacrylate ALG IRR RES Carcinogen NTP IARC OSHA

SECTION 4 – FIRST AID MEASURES

Ingestion: Ingestion is not likely. See supplemental page for emergency procedures.

Inhalation: Evacuate from further exposure. If unconsciousness occurs, seek immediate

medical assistance and call a physician. If the breath has stopped, have artificial respiration.

If breathing difficulty occurs, have oxygen inhalation.

Skin contact: Remove contaminated clothing. Wash contact areas with soap and much water.

Eye contact: Flush thoroughly with fresh water for at least 15 min. Get medical assistance immediatelyIngestion :

Get medical attention immediately.

SECTION 5 – FIRE FIGHTING MEASURES

Flash Point: Above 95℃ Method:Cleveland open cup. (Recommended)
Extinguishing agents: Carbon dioxide, form ,dry chemical
Special firefighting procedures: Not available
*Hazardous products formed by fire or thermal decomposition. Irritating organic fragments.
Unusual fire or explosion hazardsNone

Explosive Limits:

(%by volume in air) Lower Not available (%by volume in air) Upper Not available

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Evacuate non essential personnel.

Shut off all sources of ignition: No fires, smoking or flames in area.

*Ventilate area after material pick up is completed.

For small spills: Absorb spill with inert material (dry cloth, dry sand),

then place in a chemical waste containers using non-sparking tools.

Flush residual spill (area) with plenty of water.

For large spills: Dike for later disposal. Wash with plenty of water.

SECTION 7 – HANDLING AND STORAGE

Handling: Keep away from sources of ignition and heat. No smoking or flames in working area.

Take precautionary measures against static discharges.

Avoid contact with skin and eyes.

Wear proper protective equipment.

Use only in well ventilated areas.

Use exhaust ventilation to keep air concentration below exposure limit.

Keep container tightly closed when not in use.

Install emergency showers and eye wash facility in working area.

Storage: Keep away from all possible source of ignition.

Store in a cool, dry, well ventilated location.

Keep container tightly closed.

Keep away from combustible materials, heat, steam pipe or sunlight.

Keep away from oxidizing materials.

Other Precautions:

Wash hands, face and gargle after work.

Practice good personal hygiene after using this material, especially before eating, drinking,

smoking or using the rest room.

Keep out of reach of children.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection (Specify type): Chemical cartridge respirator with organic vapor. Local exhausts *Special Should be used control vapors in work area. Mechanical (General) *Other Should use a breathing mask. Protective gloves: Polyethylene gloves. No rubber. Eye protection: Safety glasses, face shield. Skin protection: Other protective clothing or equipment impervious clothing, apron and boots. Barrier creams, etc.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Black liquid Odor: Odorless, irritating. Boiling point: Above 190°C Melting point: N/A Specific gravity (H2O =1):0.9 ~ 1.1 Vapor pressure (at25°C): 1Pa Vapor density (Air =1): 4.9 Evaporation rate (Butyl acetate =1): N/A Solubility in water: Insoluble(polymerized by water)

SECTION 10 - STABILITY AND REACTIVITY

Condition to avoid: High humidity, high temperature or direct sunlight.
Stability: Stable (cool and dry area.).
Materials to avoid: Polymerized by contact with water, alcohols, amines, alkalies.
Hazardous decomposition or byproducts: CO2, oxides and nitrogen and unknown hydrocarbons.

SECTION 11 – TOXICOLOGICAL INFORMATION

Toxicity: Skin contact may cause burns. Bond skin rapidly and strongly.
Skin and eye may be irritant.
Oral LD50: 6760mg /kg in rat. (Acute) (Pro forma amount)allied substance
Routes of entry: Inhalation (Yes), Skin (Yes), Ingestion (Yes)
Carcinogen etc: See Section 3

SECTION 12 – ECOLOGICAL INFORMATION

None known

SECTION 13 – DISPOSAL INFORMATION

Waste disposal method:

Don't pour drain. Follow domestic and local environmental regulations. Precautions to be taken in handling and storing. Avoid unnecessary exposure to air and moisture.Don't store above 25 $^{\circ}$ C and in direct sunlight, Keep container lids tightly closed.

Other Precautions:

Avoid contact with skin and eyes. Protect eyes, skin and clothing from contact with liquid product.Wear recommended equipment.

SECTION 14 – TRANSPORT INFORMATION

IATA: Not restricted CLASS: Unlisted UN Number: Unlisted

DOT (49 CFR 172) *Domestic ground transport **Proper shipping name**: Unrestricted (Not more than 450 liters.) Combustible liquids n.o.s.(Cyanoacrylate ester) (More than 450 liters) **Hazard class or division**: Unrestricted (Not more than 450 liters.) Combustible liquids. (More than 450 liters) **Identification number**: None (Not more than 450 liters.) NA1993 (More than 450 liters) Marine pollutant: None. Proper shipping name: Unrestricted Class or division: Unrestricted UN or ID number: None

SECTION 15 – REGURATORY INFORMATION

CA Proportion 65:

No California proposition 65 chemicals are known to be present.

SECTION 16 – OTHER INFORMATION

Estimated NFPA Code: *NFPA is a registered trademark of the National Fire Protection Assn. Health Hazard: 2 Fire Hazard: 2 Reactivity Hazard: 1 Specific Hazard: Does not apply Estimated HMIS Code: *HMIS is a registered trademark of the National Paint and Coatings Assn. Health Hazard: 2 Flammability Hazard: 2

Note

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Paradise Visage Kft. It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Paradise Visage Kft assume no responsibility for use or reliance upon this information.